

H5E_PRINT1

[Expand all](#) [Collapse all](#)

- [Jump to ...](#)
- [Summary](#)
- [Description](#)
- [Example](#)
- [Switch language ...](#)
- [C](#)
- [C++](#)
- [FORTRAN](#)
- [JAVA](#)

[Summary](#)
[Description](#)
[Example](#)
[JAVA](#)
[FORTRAN](#)
[C++](#)
[C](#)

H5E_PRINT1

Prints the current error stack in a default manner

This function is deprecated in favor of the function [H5E_PRINT2](#) or the macro [H5E_PRINT](#).

Procedure:

H5E_PRINT1(stream)

Signature:

```
herr_t H5Eprint1(FILE * stream)
```

```
SUBROUTINE h5eprint_f(hdferr, name)
  CHARACTER(LEN=*) OPTIONAL, INTENT(IN) :: name ! File name
  INTEGER, INTENT(OUT) :: hdferr ! Error code
END SUBROUTINE h5eprint_f
```

Parameters:

<i>FILE</i> *stream	IN: File pointer, or stderr if NULL
---------------------	-------------------------------------

Description:

H5E_PRINT1 prints the error stack for the current thread on the specified stream, `stream`. Even if the error stack is empty, a one-line message will be printed:

```
HDF5-DIAG: Error detected in thread 0.
```

H5E_PRINT1 is a convenience function for H5E_WALK1 with a function that prints error messages. Users are encouraged to write their own more specific error handlers.

Returns:

Returns a non-negative value if successful; otherwise returns a negative value.

Example:

Coming Soon!

History:

Release	C
1.8.0	Function <code>H5Eprint</code> renamed to <code>H5Eprint1</code> and deprecated in this release.

--- Last Modified: April 13, 2018 | 01:52 PM