

H5P_GET_ELINK_FAPL

[Expand all](#) [Collapse all](#)

- [Jump to ...](#)
- [Summary](#)
- [Description](#)
- [Example](#)
- [Switch language ...](#)
- [C](#)
- [C++](#)
- [FORTRAN](#)
- [JAVA](#)

[Summary](#)
[Description](#)
[Example](#)
[JAVA](#)
[FORTRAN](#)
[C++](#)
[C](#)

H5P_GET_ELINK_FAPL

Retrieves the file access property list identifier associated with the link access property list

Procedure:

H5P_GET_ELINK_PREFIX (lapl_id)

Signature:

```
hid_t H5Pget_elink_prefix(  
    hid_t lapl_id  
)
```

NONE

Parameters:

hid_t lapl_id IN: Link access property list identifier

Description:

H5P_GET_ELINK_FAPL retrieves the file access property list identifier that is set for the link access property list identifier, lapl_id. The library uses this file access property list identifier to open the target file for the external link access. See also [H5P_SET_ELINK_FAPL](#) and [H5L_CREATE_EXTERNAL](#). When no such identifier is set, this routine returns H5P_DEFAULT.

Returns:

Returns a non-negative value if successful; otherwise returns a negative value.

Example:

Coming Soon!

History:

Release	Change
1.8.0	Function introduced in this release.

--- Last Modified: August 06, 2019 | 02:05 PM