

H5IM_GET_NPALETTES

[Expand all](#) [Collapse all](#)

- [Jump to ...](#)
- [Summary](#)
- [Description](#)
- [Example](#)
- [Switch language ...](#)
- C
- C++
- FORTRAN
- JAVA

[Summary](#)

[Description](#)

[Example](#)

[JAVA](#)

[FORTRAN](#)

[C++](#)

[C](#)

H5IM_GET_NPALETTES

Gets the number of palettes associated to an image.

Procedure:

`H5IM_GET_NPALETTES(loc_id, image_name, npals)`

Signature:

```
herr_t H5IMget_npalettes( hid_t loc_id, const char *image_name, hssize_t *npals )

subroutine h5imget_npalettes_f(loc_id, dset_name, npals, errcode)
  implicit none
  integer(HID_T), intent(IN) :: loc_id          ! file or group identifier
  character(LEN=*), intent(IN) :: dset_name      ! name of the dataset
  integer(HSIZE_T), intent(INOUT) :: npals        ! palettes
  integer :: errcode                          ! error code
end subroutine h5imget_npalettes_f
```

Parameters:

<code>hid_t loc_id</code>	IN: Identifier of the file or group in which the image dataset is located.
<code>const char *image_name</code>	IN: The name of the image dataset.
<code>hssize_t *npals</code>	OUT: The number of palettes.

Description:

H5IMget_npalettes gets the number of palettes associated to an image specified by `image_name`.

Returns:

Returns a non-negative value if successful; otherwise returns a negative value.

Example:

Coming Soon!

--- Last Modified: December 04, 2017 | 07:19 AM