

# H5P\_SET\_CREATE\_INTERMEDIATE\_GROUP

[Expand all](#) [Collapse all](#)

- [Jump to ...](#)
- [Summary](#)
- [Description](#)
- [Example](#)
- [Switch language ...](#)
- [C](#)
- [C++](#)
- [FORTRAN](#)
- [JAVA](#)

[Summary](#)  
[Description](#)  
[Example](#)  
[JAVA](#)  
[FORTRAN](#)  
[C++](#)  
[C](#)

# H5P\_SET\_CREATE\_INTERMEDIATE\_GROUP

Specifies in property list whether to create missing intermediate groups

## Procedure:

H5P\_SET\_CREATE\_INTERMEDIATE\_GROUP ( lcpl\_id, crt\_intermed\_group )

## Signature:

```
herr_t H5Pset_create_intermediate_group(  
    hid_t lcpl_id,  
    unsigned crt_intermed_group  
)
```

Fortran90 Interface: h5pset\_create\_inter\_group\_f

```
SUBROUTINE h5pset_create_inter_group_f(lcpl_id, crt_intermed_group, hdferr)  
    IMPLICIT NONE  
    INTEGER(HID_T), INTENT(IN) :: lcpl_id  
        ! Link creation property list identifier  
    INTEGER, INTENT(IN) :: crt_intermed_group  
        ! Specifying whether to create intermediate groups  
        ! upon the creation of an object  
    INTEGER, INTENT(OUT) :: hdferr  
        ! Error code  
        ! 0 on success and -1 on failure  
END SUBROUTINE h5pset_create_inter_group_f
```

## Parameters:

<i>hid_t</i> <code>lcpl_id</code>	IN: Link creation property list identifier
<i>unsigned</i> <code>crt_intermed_group</code>	IN: Flag specifying whether to create intermediate groups upon the creation of an object

## Description:

`H5P_SET_CREATE_INTERMEDIATE_GROUP` specifies whether to set the link creation property list `lcpl_id` so that calls to functions that create objects in groups different from the current working group will create intermediate groups that may be missing in the path of a new or moved object.

Functions that create objects in or move objects to a group other than the current working group make use of this property. [H5G\\_CREATE\\_ANON](#) and [H5L\\_MOVE](#) are examples of such functions.

If `crt_intermed_group` is positive, the `H5G_CREATE_INTERMEDIATE_GROUP` will be added to `lcpl_id` (if it is not already there). Missing intermediate groups will be created upon calls to functions such as those listed above that use `lcpl_id`.

If `crt_intermed_group` is non-positive, the `H5G_CREATE_INTERMEDIATE_GROUP`, if present, will be removed from `lcpl_id`. Missing intermediate groups will *not* be created upon calls to functions such as those listed above that use `lcpl_id`.

## Returns:

Returns a non-negative value if successful; otherwise returns a negative value.

## Example:

The following call sets the link creation property list `lcpl_id` such that a call to [H5G\\_CREATE\\_ANON](#) or other function using `lcpl_id` will create any missing groups in the path to the new object:

```
herr_t ret_value = H5Pset_create_intermediate_group(lcpl_id, 1)
```

## History:

Release	Change
1.8.0	Function introduced in this release.