

H5F_SET_LATEST_FORMAT

[Expand all](#) [Collapse all](#)

- [Jump to ...](#)
- [Summary](#)
- [Description](#)
- [Example](#)
- [Switch language ...](#)
- [C](#)
- [C++](#)
- [FORTRAN](#)
- [JAVA](#)

[Summary](#)
[Description](#)
[Example](#)
[JAVA](#)
[FORTRAN](#)
[C++](#)
[C](#)

H5F_SET_LATEST_FORMAT

Enables the switching between latest or non-latest format for an opened file (DEPRECATED)

This function is deprecated in favor of the function [H5F_SET_LIBVER_BOUNDS](#)

Procedure:

H5F_SET_LATEST_FORMAT (file_id, latest_format)

Signature:

```
herr_t H5Fset_latest_format(  
    hid_t file_id,  
    hbool_t latest_format  
)
```

Parameters:

`hid_t file_id` IN: A file identifier
`hbool_t latest_format` IN: Enable latest format or not

Description:

H5F_SET_LATEST_FORMAT enables the switching between latest or non-latest format for an opened file associated with `file_id`.

Returns:

Returns a non-negative value if successful; otherwise returns a negative value.

Example:

Coming Soon!

History:

Release	Change
1.10.2	Function deprecated.
1.10.0	Function introduced in this release.

--- Last Modified: December 20, 2018 | 12:27 PM