

H5P_GET_LINK_CREATION_ORDER

[Expand all](#) [Collapse all](#)

- [Jump to ...](#)
- [Summary](#)
- [Description](#)
- [Example](#)
- [Switch language ...](#)
- [C](#)
- [C++](#)
- [FORTRAN](#)
- [JAVA](#)

[Summary](#)
[Description](#)
[Example](#)
[JAVA](#)
[FORTRAN](#)
[C++](#)
[C](#)

H5P_GET_LINK_CREATION_ORDER

Queries whether link creation order is tracked and/or indexed in a group

Procedure:

H5P_GET_LINK_CREATION_ORDER (gcpl_id, crt_order_flags)

Signature:

```
herr_t H5Pget_link_creation_order(  
    hid_t gcpl_id,  
    unsigned *crt_order_flags  
)
```

Parameters:

<i>hid_t</i> gcpl_id	IN: Group or file creation property list identifier
<i>unsigned</i> *crt_order_flags	OUT: Creation order flag(s)

Description:

H5P_GET_LINK_CREATION_ORDER queries the group or file creation property list, `gcpl_id`, and returns a flag indicating whether link creation order is tracked and/or indexed in a group.

See [H5P_SET_LINK_CREATION_ORDER](#) for a list of valid creation order flags, as passed in `crt_order_flags`, and their meanings.

Returns:

Returns a non-negative value if successful; otherwise returns a negative value.

Example:

Coming Soon!

History:

Release	Change
1.8.0	Function introduced in this release.

--- Last Modified: January 03, 2020 | 10:12 AM